

PK70.030C1

7 "STD Camera Kit - 4C, Multiple view

NBS Cam

Avoid blind spots!

Characteristics

- ✦ 7 "color digital display
- ✦ Multiple view monitor, 4 channels
- ✦ Single, dual, triple, quad, trefoil display
- ✦ 4 entrées de caméra, 1 entrée vidéo
- ✦ Built-in microphone and speaker
- ✦ Camera housing heating under 10°C
- ✦ Brightness automatic adjustment Day / night
- ✦ 1 year warranty
- ✦ Cable: 5m, 10m, 15m, 20m (option)



Specifications

Camera

CC100

Image Device:	Color CCD
Housing:	Heating (under 10 ° C)
Lens angle:	120°
Waterproof:	IP69K
Operating Temperature:	-30 to +70°C
Storage Temperature:	-40 to +70°C
Power source:	12-24 VDC
Resolution:	600 TV line
Array size:	976x494 pixels
Night vision distance:	12-15m (IR-CUT)
Picture image:	Normal / Mirror
Audio:	Built-in microphone
Material:	Ionized aluminum
TV system:	PAL / NTSC
Connection:	RCA / 4 pins
Anti-vibration	10g
Certification:	CE, EMARK, FCC
Weight (lbs / kg):	1.23 / 0.56
Size (cm):	11.6x8.5x7.9

Monitor

MC736

Size:	7"
Type:	Color LCD
Picture image :	Multiple (4 channels)
Operating Temperature:	-20° to +70°C
Storage Temperature :	-30°C to + 80°C (RH90%)
Power source:	12-24 VDC
Resolution:	800x3 (RGB) x 480
DOT pitch:	0.0642 (L) x 0.1790 (H)
Brightness:	400 cdm2
Contrast:	500: 1
Audio:	Built-in speaker (1.5W)
Video inputs:	4x cameras, 1x DVD, 1 AUX
Audio outputs:	4x cameras, 1x DVD
Power consumption:	Max 25W
Viewing angle:	U: 50° D: 70° R/L: 70°
Anti vibration:	3g (center mount bracket) / 7g (U support)
Weight (lbs / kg):	3.53 /1.6
Outside sizes (mm):	
Without flush mount:	182 (L) x 122 (H) x 26 (P)
With flush mount	198 (L) x 138 (H) x 31 (P)

* 9" monitor available - MC746