

PK73.030B1

7" HD Camera Kit - Multiple view

NBS Cam

Avoid blind spots!



Characteristics

- ◆ 7 " touchscreen color digital display (1080P)
- ◆ Multiple view monitor, 4 channels
- ◆ Single, dual, triple, quad, trefoil display
- ◆ camera inputs, 1 video input
- ◆ Built-in microphone and speaker
- ◆ Camera housing heating under 10°C
- ◆ Brightness automatic adjustment Day / night
- ◆ 1 year warranty
- ◆ Cable: 5m, 10m, 15m, 20m (option)

Specifications

Camera

CH100

Image Device:	Color CCD
Housing:	Heating (under 10 ° C)
Lens angle:	120°
Waterproof:	IP69K
Operating Temperature:	-30 to +70°C
Storage Temperature:	-40 to +70°C
Power source:	12-24 VDC
Resolution:	600 TV line
Array size:	976x494 pixels
Night vision distance:	12-15m (IR-CUT)
Picture image:	Normal / Mirror
Audio:	Built-in microphone
Material:	Ionized aluminum
TV system:	PAL / NTSC
Connection:	RCA / 4 pins
Anti-vibration	10g
Certification:	CE, EMARK, FCC
Weight (lbs / kg):	1.23 / 0.56
Size (cm):	11.6x8.5x7.9

Monitor

MH964*

Size:	7"
Type:	Touchscreen - Color LCD
Picture image:	Multiple
Number of channel:	4
Operating Temperature:	-20 to +70°C (RH90%)
Storage Temperature:	-30°C to + 80°C (RH90%)
Power source:	12-24 VDC
Resolution:	1024x3 (RGB) x 600
DOT pitch:	0.1506 (W) x 0.1432 (H)
Brightness:	500 cd/m ²
Contrast:	800: 1
Audio:	Built-in speaker (1.5W)
Power consumption::	Max 8W
Viewing angle:	U: 85° D: 85° R/L: 85° / 85°
Anti vibration:	3g (center mount bracket) / 7g (U support)
Weight (lbs / kg):	3.53 / 1.6
Outside sizes (mm):	203 (W) x 112 (H) x 28 (T)

* 10.1" monitor available - MH991