

PK71.130B1

9" Wireless Camera Kit - Vue multiple

NBS Cam

Avoid blind spots!



Characteristics

- ❖ 9" color LCD wireless display
- ❖ Monitor Quad-view, 4 channels
- ❖ Recording function
- ❖ Water resistant camera housing.
- ❖ Brightness automatic adjustment day / night
- ❖ 1 year warranty
- ❖ Transmission range: 80m (120m option)

Specifications

Camera

CW325

Image Device :	Color CCD
Lens angle:	120°
Waterproof:	IP69K
Operating Temperature:	-20°C to +70°C
Storage Temperature:	-30°C to +80°C
Power Supply:	12-24 VDC
Resolution:	500 TV line
Array size:	976x494 pixels
Night vision distance	10M (IR-CUT)
Picture image:	Normal / Mirror
Audio:	Built-in microphone
Material:	Ionized aluminum
TV system:	PAL / NTSC
Transmission Range:	80m (5" antenna) (without obstacle) 120m (8" antenna - Option)
Current Consumption:	Max. 250mA@12V / 140mA@24V
Operating frequency:	2400 - 2483.5 MHz
Receiving sensitivity :	-89 dBm
Emitting frequency:	17 dBm
Decompression form:	MPEG4

Monitor

MWQ838

Size:	9"
Type:	Color LCD
Picture image:	Quad-view
Channel:	4
Operating temperature:	-20°C to +70°C
Storage temperature:	-30°C to + 80°C (RH90%)
Power supply:	12-24VDC
Resolution:	800x3 (RGB) x 480
DOT pitch:	0.0642 (L) x 0.1790 (H)
Brightness:	400 cdm ²
Contrast:	500: 1
Audio:	Haut-parleur intégré (1.5W/8Ω)
Modulation:	2.4Gz
Operating Frequency:	2400 - 2483.5 MHz
Emitting frequency:	17 dBm
Power Consumption:	about 6W
Viewing angle:	U: 50° D: 70° R/L: 70°
Transmission range:	120M (without obstacle)
Receiving sensitivity:	-89 dBm
Decompression form:	MPEG4

* 7" monitor available - MWQ827