

# PK70.010A1

## 7" STD Camera Kit - 1C, Single view

# NBS Cam

Avoid blind spots!



### Characteristics

- ✦ 7" color digital display
- ✦ Single view monitor, 1 channel
- ✦ Built-in microphone and speaker
- ✦ 120° field of view
- ✦ Camera housing heating under 10°C
- ✦ Brightness automatic adjustment Day / night
- ✦ 1 year warranty
- ✦ Cable: 5m, 10m, 15m, 20m (option)

### Specifications

#### Camera

#### CC100

Image Device:	Color CCD
Housing:	Heating (under 10 ° C)
Lens angle:	120°
Waterproof:	IP69K
Operating Temperature:	-30 to +70°C
Storage Temperature:	-40 to +70°C
Power source:	12-24 VDC
Resolution:	600 TV line
Array size:	976x494 pixels
Night vision distance:	12-15m (IR-CUT)
Picture image:	Normal / Mirror
Audio:	Built-in microphone
Material:	Ionized aluminum
TV system:	PAL / NTSC
Connection:	RCA / 4 pins
Anti-vibration	10g
Certification:	CE, EMARK, FCC
Weight (lbs / kg):	1.23 / 0.56
Size (cm):	11.6x8.5x7.9

#### Monitor

#### MC727

Size:	7"
Type:	Color LCD
Picture image:	Single
Channel:	1
Operating Temperature:	-20° to +70°C (RH90%)
Storage Temperature:	-30°C to + 80°C (RH90%)
Power source:	12-24 VDC
Resolution:	800x3 (RGB) x 480
DOT pitch:	0.0642 (L) x 0.1790 (H)
Brightness:	400 cdm2
Contrast:	500: 1
Audio:	Built-in speaker (1.5W)
Power consumption:	about 6W
Viewing angle:	U: 50° D: 70° R/L: 70° / 70°
Anti vibration:	3g (center mount bracket / 7g (U support)
Weight (lbs / kg):	3.75 / 1.7
Outside sizes (mm):	
Without flush mount :	182 (L) x 122 (H) x 26 (P)
With flush mount:	198 (L) x 138 (H) x 31 (P)

\*9" monitor available - MC738